

MATERIALS	
PL	NYLON

SEPARATOR							
CODE			DIMENSIONS (mm)				Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	MIN HOLE DEPTH	HOLE Ø	MAX FIXING THICKNESS	
AC	PL	TAS 005025 0000 00	25	35	5	1.5	100
AC	PL	TAS 006030 0000 00	30	40	6	6	100
AC	PL	TAS 008040 0000 00	40	55	8	5	50
AC	PL	TAS 010070 0000 00	50	70	10	4	25

Complete with clipboard screw



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

METALLIC EXPANSION ANCHOR DV-LEX							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø			
AC	ZE	TAS 0M6045 TOP0 00	45	10	M6 X 55	100	
AC	ZE	TAS 0M8050 TOP0 00	51	12	M8 X 65	100	
AC	ZE	TAS M10060 TOP0 00	60	14	M10 X 80	50	
AC	ZE	TAS M12075 TOP0 00	75	18	M12 X 100	25	

Suitable for non-cracked concrete, solid brick, natural stone
Complete with hexagonal bolt. Stainless steel on request.



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

HEAVY DUTY ANCHOR FOR HOLLOW CEILING SLABS							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø			
AC	ZE	TAS 0M6038 APSA 00	38	10	M6	100	
AC	ZE	TAS 0M8043 APSA 00	43	12	M8	100	
AC	ZE	TAS 0M1052 APSA 00	52	14	M10	50	

Stainless steel on request



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

ZAMA EXPANSION HEAVY DUTY ANCHOR							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICNKESS		
AC	ZE	TAS 0M6047 APIZ 00	47	12	10	M6 X 55	100
AC	ZE	TAS 0M8050 APIZ 00	50	14	15	M8 X 70	100
AC	ZE	TAS 0M1057 APIZ 00	57	16	20	M10 X 80	50
AC	ZE	TAS 0M12072 APIZ 00	72	20	20	M12 X 100	25
AC	ZE	TAS 0M16107 APIZ 00	107	25	20	M16 X 150	25

Suitable for non-cracked, solid brick, natural stone



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

4 SEGMENTS HEAVY DUTY STEEL ANCHOR							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICNKESS		
AC	ZE	TAS 0M6040 AP4S 00	40	10	15	M6 X 55	100
AC	ZE	TAS 0M8050 AP4S 00	50	14	20	M8 X 70	100
AC	ZE	TAS 0M8060 AP4S 00	60	16	20	M10 X 80	50
AC	ZE	TAS 0M8080 AP4S 00	80	20	20	M12 X 100	25
AC	ZE	TAS 0M8100 AP4S 00	100	25	25	M16 X 150	25

Suitable for non-cracked, solid brick, natural stone



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

SHERARDISE HEAVY DUTY STEEL ANCHOR							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICNKESS		
AC	ZE	TAS 0M6040 AP4S 00	40	10	15	M6 X 55	100
AC	ZE	TAS 0M8050 AP4S 00	50	14	20	M8 X 70	100
AC	ZE	TAS 0M8060 AP4S 00	60	16	20	M10 X 80	50
AC	ZE	TAS 0M8080 AP4S 00	80	20	20	M12 X 100	25
AC	ZE	TAS 0M8100 AP4S 00	100	25	25	M16 X 150	25

Suitable for non-cracked, solid brick, natural stone



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

SAFETY STEEL ANCHOR FIXING IN SEISMIC ZONE							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	TAS M06070 APIS 00	70	10	10	M6 X 70	50
AC	ZE	TAS M06080 APIS 00	80	10	20	M6 X 80	50
AC	ZE	TAS M06110 APIS 00	110	10	50	M6 X 110	50
AC	ZE	TAS M08080 APIS 00	80	12	10	M8 X 80	50
AC	ZE	TAS M08090 APIS 00	90	12	20	M8 X 90	50
AC	ZE	TAS M08120 APIS 00	120	12	50	M8 X 120	50
AC	ZE	TAS M10090 APIS 00	90	15	10	M10 X 90	50
AC	ZE	TAS M10100 APIS 00	100	15	20	M10 X 100	50
AC	ZE	TAS M10130 APIS 00	130	15	50	M10 X 130	25
AC	ZE	TAS M12120 APIS 00	110	18	10	M12 X 120	25
AC	ZE	TAS M12130 APIS 00	125	18	25	M12 X 130	25
AC	ZE	TAS M12160 APIS 00	150	18	50	M12 X 160	25
AC	ZE	TAS M12200 APIS 00	200	18	100	M12 X 200	25

Suitable for non-cracked, concrete, natural stone



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

HEAVY DUTY EXPANSION ANCHOR							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	TAS M06070 APPE00	70	10	10	M6 X 70	50
AC	ZE	TAS M06080 APPE00	80	10	20	M6 X 80	50
AC	ZE	TAS M06110 APPE00	110	10	50	M6 X 110	50
AC	ZE	TAS M08080 APPE00	80	12	10	M8 X 80	50
AC	ZE	TAS M08090 APPE00	90	12	20	M8 X 90	50
AC	ZE	TAS M08120 APPE00	120	12	50	M8 X 120	50
AC	ZE	TAS M10090 APPE00	90	15	10	M10 X 90	50
AC	ZE	TAS M10100 APPE00	100	15	20	M10 X 100	50
AC	ZE	TAS M10130 APPE00	130	15	50	M10 X 130	25
AC	ZE	TAS M12110 APPE00	110	18	10	M12 X 120	25
AC	ZE	TAS M12125 APPE00	125	18	25	M12 X 130	25
AC	ZE	TAS M12150 APPE00	150	18	50	M12 X 160	25
AC	ZE	TAS M12200 APPE00	200	18	100	M12 X 200	25

Suitable for non-cracked, concrete, natural stone




MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

SHERARDISE HEAVY DUTY STEEL ANCHOR							
CODE			DIMENSIONS (mm)			Box/Pcs	
GROUP	MATERIAL	TYPE	SCREW LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	TAS 008065 APPD 00	65*	8	6	100	
AC	ZE	TAS 008080 APPD 00	80*	8	6	100	
AC	ZE	TAS 008075 APPD 00	75*	10	10	100	
AC	ZE	TAS 008110 APPD 00	110*	10	10	100	
AC	ZE	TAS 008085 APPD 00	85*	12	25	50	
AC	ZE	TAS 008120 APPD 00	120*	12	25	50	
AC	ZE	TAS 008100 APPD 00	100	14	50	50	
AC	ZE	TAS 008130 APPD 00	130	14	50	50	
AC	ZE	TAS 008110 APPD 00	110	16	85	50	
AC	ZE	TAS 008130 APPD 00	130	16	85	50	

Suitable for non-cracked, concrete, natural stone

* Available in stainless steel on request



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

SAFETY STEEL ANCHOR FIXING IN SEISMIC ZONE							
CODE			DIMENSIONS (mm)			THREAD	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	TAS M10090 AAZS 00	90	10	10	M10	100
AC	ZE	TAS M10095 AAZS 00	95	10	15	M10	100
AC	ZE	TAS M10100 AAZS 00	100	10	20	M10	100
AC	ZE	TAS M10110 AAZS 00	110	10	30	M10	100
AC	ZE	TAS M10130 AAZS 00	130	10	50	M10	100
AC	ZE	TAS M10155 AAZS 00	155	10	75	M10	100
AC	ZE	TAS M10180 AAZS 00	180	10	100	M10	100
AC	ZE	TAS M12105 AAZS 00	105	12	10	M12	50
AC	ZE	TAS M12110 AAZS 00	110	12	15	M12	50
AC	ZE	TAS M12115 AAZS 00	115	12	20	M12	50
AC	ZE	TAS M12125 AAZS 00	125	12	30	M12	50
AC	ZE	TAS M12125 AAZS 00	145	12	50	M12	50
AC	ZE	TAS M12160 AAZS 00	160	12	65	M12	50
AC	ZE	TAS M12180 AAZS 00	180	12	85	M12	50
AC	ZE	TAS M12200 AAZS 00	200	12	105	M12	50

Suitable for non-cracked, solid brick, natural stone



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

EXPANSION ANCHOR							
CODE			DIMENSIONS (mm)			THREAD	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	TAS M06055 AP00 00	55	6	10	M6	100
AC	ZE	TAS M06080 AP00 00	80	8	15	M8	100
AC	ZE	TAS M06095 AP00 00	95	8	30	M8	100
AC	ZE	TAS M06155 AP00 00	115	8	50	M8	100
AC	ZE	TAS M10090 AP00 00	90	10	15	M10	100
AC	ZE	TAS M10120 AP00 00	120	10	45	M10	50
AC	ZE	TAS M10150 AP00 00	150	10	75	M10	50
AC	ZE	TAS M10110 AP00 00	110	12	15	M12	50
AC	ZE	TAS M12120 AP00 00	120	12	25	M12	50
AC	ZE	TAS M12140 AP00 00	140	12	45	M12	50
AC	ZE	TAS M12160 AP00 00	160	12	65	M12	50

Suitable for non-cracked, solid brick, natural stone



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

EXPANSION ANCHOR WITH EXTRA FAST DOUBLE CLIP							
CODE			DIMENSIONS (mm)			THREAD	Box/Pcs
GROUP	MATERIAL	TYPE	SCREW LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	TAS M06045 AEDF 00	45	6	5	M6	100
AC	ZE	TAS M08065 AEDF 00	65	6	15	M8	100
AC	ZE	TAS M08055 AEDF 00	55	8	5	M8	100
AC	ZE	TAS M08075 AEDF 00	75	8	10	M8	100
AC	ZE	TAS M08095 AEDF 00	95	8	25	M8	100
AC	ZE	TAS M08115 AEDF 00	115	8	50	M8	100
AC	ZE	TAS M10065 AEDF 00	65	10	10	M10	100
AC	ZE	TAS M10090 AEDF 00	90	10	20	M10	100
AC	ZE	TAS M10120 AEDF 00	120	10	40	M10	50
AC	ZE	TAS M12075 AEDF 00	75	12	5	M12	50
AC	ZE	TAS M12110 AEDF 00	110	12	15	M12	50
AC	ZE	TAS M12145 AEDF 00	145	12	25	M12	50
AC	ZE	TAS M12180 AEDF 00	180	12	80	M12	50

Suitable for non-cracked, solid brick, natural stone



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

TCM DOWELS FOR HEAVY DUTY							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	TAS 0M6080 0000 00	80	6	25	M6	100
AC	ZE	TAS 0M8055 0000 00	55	8	5	M8	100
AC	ZE	TAS 0M8060 0000 00	60	8	10	M8	100
AC	ZE	TAS 0M8075 0000 00	75	8	15	M8	100
AC	ZE	TAS 0M8090 0000 00	90	8	25	M8	100
AC	ZE	TAS M10065 0000 00	65	10	5	M10	100
AC	ZE	TAS M10080 0000 00	80	10	10	M10	100
AC	ZE	TAS M10090 0000 00	90	10	20	M10	100
AC	ZE	TAS M10120 0000 00	120	10	50	M10	50
AC	ZE	TAS M12090 0000 00	90	12	15	M12	50
AC	ZE	TAS M12110 0000 00	110	12	20	M12	50
AC	ZE	TAS M12120 0000 00	120	12	30	M12	50
AC	ZE	TAS M12145 0000 00	145	12	50	M12	25
AC	ZE	TAS M12160 0000 00	160	12	65	M12	25
AC	ZE	TAS M12180 0000 00	180	12	85	M12	25
AC	ZE	TAS M12200 0000 00	200	12	100	M12	25

Suitable for concrete

Available in stainless steel on request



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

CONCRETE SCREWS							
CODE			DIMENSIONS (mm)			SCREW	Box/Pcs
GROUP	MATERIAL	TYPE	ANCHOR LENGHT	HOLE Ø	MAX FIXING THICKNESS		
AC	ZE	VPC M08080 0000 00	80	6	20	M8	100
AC	ZE	VPC M08100 0000 00	100	6	40	M8	100
AC	ZE	VPC M08120 0000 00	120	6	60	M8	100
AC	ZE	VPC M10080 0000 00	80	8	10	M10	100
AC	ZE	VPC M10100 0000 00	100	8	30	M10	100
AC	ZE	VPC M10120 0000 00	120	8	50	M10	100
AC	ZE	VPC M10140 0000 00	140	8	70	M10	100
AC	ZE	VPC M10160 0000 00	160	8	90	M10	50
AC	ZE	VPC M12080 0000 00	90	10	10	M12	50
AC	ZE	VPC M12110 0000 00	110	10	30	M12	50
AC	ZE	VPC M12130 0000 00	130	10	50	M12	50
AC	ZE	VPC M12150 0000 00	150	10	70	M12	50
AC	ZE	VPC M12190 0000 00	190	10	110	M12	50

Suitable for concrete



MATERIALS	
ZE	ELECTROLYTIC GALVANIZED STEEL

CONCRETE DOWELS							
CODE			DIMENSIONS (mm)		SCREW	Box/Pcs	
GROUP	MATERIAL	TYPE	SCREW LENGHT	HOLE Ø			
AC	ZE	TAS 0M6000 AAPE 00	25	8	M6	100	
AC	ZE	TAS 0M8000 AAPE 00	30	10	M8	100	
AC	ZE	TAS 0M1000 AAPE 00	40	12	M12	50	
AC	ZE	TAS 0M1200 AAPE 00	50	15	M15	25	

Suitable for non-cracked concrete