


NYLON CABLE TIES						
CODE			DIMENSIONS (mm)			Box/Pcs
GROUP	MATERIAL	TYPE	LENGHT	WIDTH	MIN. LOAD	
AC	PL	FAS 075024 0000 00	75	2,4	8	100/1000
AC	PL	FAS 096025 0000 00	96	2,5	8	100/1000
AC	PL	FAS 120025 0000 00	120	2,5	8	100/1000
AC	PL	FAS 120048 0000 00	120	4,8	22	100/1000
AC	PL	FAS 140025 0000 00	140	2,5	8	100/1000
AC	PL	FAS 140032 0000 00	140	3,2	18	100/1000
AC	PL	FAS 165025 0000 00	165	2,5	8	100/1000
AC	PL	FAS 160048 0000 00	160	4,8	22	100/1000
AC	PL	FAS 200025 0000 00	200	2,5	8	100/1000
AC	PL	FAS 200032 0000 00	200	3,2	18	100/1000
AC	PL	FAS 200046 0000 00	200	4,6	22	100/1000
AC	PL	FAS 200076 0000 00	200	7,6	55	100/1000
AC	PL	FAS 250048 0000 00	250	4,8	22	100
AC	PL	FAS 250036 0000 00	250	3,6	18	100
AC	PL	FAS 265036 0000 00	265	3,6	18	100
AC	PL	FAS 292036 0000 00	292	3,6	18	100
AC	PL	FAS 300076 0000 00	300	7,6	55	100/1000
AC	PL	FAS 310048 0000 00	310	4,8	22	100
AC	PL	FAS 360036 0000 00	360	7,6	18	100
AC	PL	FAS 360048 0000 00	360	4,8	22	100
AC	PL	FAS 360076 0000 00	360	7,6	55	100
AC	PL	FAS 380048 0000 00	380	4,8	22	100
AC	PL	FAS 432048 0000 00	432	4,8	22	100
AC	PL	FAS 550008 0000 00	550	8	80	100
AC	PL	FAS 762009 0000 00	762	9	80	50
AC	PL	FAS 914009 0000 00	914	9	80	50

MATERIALS	
PL	PLASTIC

Material: Nylon 6.6 – V2 UL94 self-extinguishing – Temperature range -40° +85° - UV resistant.

Stainless Steel AISI 304 or 316 upon request



TERMINAL EDGE PROTECTOR ROLL		
CODE		
GROUP	MATERIAL	TYPE
AC	PV	PRZ 000000 0000 00

MATERIALS	
PV	VULCANIZED PLASTIC