

DRAIN and BREATHER



Execution:

Ex d / Ex e IIC Gb
Ex tb IIIC Db IP66

Protection degree: IP66

Atex applicable standards:

EN 60079-0, EN 60079-1, EN 60079-31

IECEX applicable standards:

IEC 60070-0, IEC 60079-1, IEC 60079-31

Ambient temperature:

-50°C / +130°C

Installation area: zone 1 – 2 (Gas)

zone 21 – 22 (Dust)

Material: Stainless steel

CODE	STAINLESS STEEL	
	THREAD TYPE	SIZE
08.18.01.03.05.00000	O-ring, star washer and locknut	M20x1,5
08.18.02.03.05.00000	-	1/2" ISO 7/1, NPT

DRAIN PLUG



Execution:

Ex e IIC Gb
Ex tb IIIC Db

Protection degree: IP66

Atex applicable standards:

EN 60079-0, EN 60079-1, EN 60079-31

IECEX applicable standards:

IEC 60070-0, IEC 60079-1, IEC 60079-31

Ambient temperature:

-60°C / +85°C

Installation area: zone 1 – 2 (Gas)

zone 21 – 22 (Dust)

Material: Stainless steel

CODE	STAINLESS STEEL	
	THREAD TYPE	SIZE
08.18.01.03.03.00000	Silicone O-ring	M20x1,5